

MOSFET - Single N-Channel

100 V, 25 mΩ, 24 A

NTTFD022N10C

General Description

This device includes two specialized N-Channel MOSFETs in a dual package. The switch node has been internally connected to enable easy placement and routing of synchronous buck converters. The control MOSFET (Q2) and synchronous (Q1) have been designed to provide optimal power efficiency.

Features

Q1: N-Channel

- Max $r_{DS(on)}$ = 25 mΩ at $V_{GS} = 10$ V, $I_D = 7.8$ A
- Max $r_{DS(on)}$ = 61 mΩ at $V_{GS} = 6$, $I_D = 3.9$ A

Q2: N-Channel

- Max $r_{DS(on)}$ = 25 mΩ at $V_{GS} = 10$ V, $I_D = 7.8$ A
- Max $r_{DS(on)}$ = 61 mΩ at $V_{GS} = 6$, $I_D = 3.9$ A
- Low Inductance Packaging Shortens Rise/Fall Times, Resulting in Lower Switching Losses
- RoHS Compliant

Applications

- Computing
- Communications
- General Purpose Point of Load

PIN DESCRIPTION

Pin	Name	Description
1, 11, 12	GND (LSS)	Low Side Source
2	LSG	Low Side Gate
3, 4, 5, 6	V + (HSD)	High Side Drain
7	HSG	High Side Gate
8, 9, 10	SW	Switching Node, Low Side Drain




ON Semiconductor®


www.onsemi.com

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
100 V	25 mΩ @ 10 V	24 A
	61 mΩ @ 6 V	

ELECTRICAL CONNECTION




Dual N-Channel MOSFET



Power Clip 33 Symmetric (WQFN12) CASE 510CJ

MARKING DIAGRAM



D022 = Specific Device Code
 A = Assembly Plant Code
 Y = Numeric Year Code
 WW = Work Week Code
 ZZ = Assembly Lot Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

NTTFD022N10C

ORDERING INFORMATION AND PACKAGE MARKING

Device	Marking	Package	Shipping†
NTTFD022N10C	D022	WQFN12 (Pb-Free)	3000 Units/ Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

MOSFET MAXIMUM RATINGS (T_A = 25°C, Unless otherwise specified)

Symbol	Parameter	Q1	Q2	Units
V _{DS}	Drain-to-Source Voltage	100	100	V
V _{GS}	Gate-to-Source Voltage	±20	±20	V
I _D	Drain Current –Continuous T _C = 25°C (Note 4)	24	24	A
	–Continuous T _C = 100°C (Note 4)	14	14	
	–Continuous T _A = 25°C	6 (Note 1a)	6 (Note 1b)	
	–Pulsed T _A = 25°C	349	349	
E _{AS}	Single Pulse Avalanche Energy (L = 3 mH, I _{L(pk)} = 5.1 A) (Note 3)	39	39	mJ
P _D	Power Dissipation for Single Operation T _C = 25°C	26	26	W
	Power Dissipation for Single Operation T _A = 25°C	1.7 (Note 1a)	1.7 (Note 1b)	
T _J , T _{STG}	Operating and Storage Junction Temperature Range	–55 to +150		°C
T _L	Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	260	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Q1	Q2	Units
R _{θJC}	Thermal Resistance, Junction-to-Case	4.8	4.8	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient	70 (Note 1a)	70 (Note 1b)	
R _{θJA}	Thermal Resistance, Junction-to-Ambient	135 (Note 1c)	135 (Note 1c)	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
--------	-----------	-----------------	------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV _{DSS}	Drain-to-Source Breakdown Voltage	I _D = 250 μA, V _{GS} = 0 V	Q1	100			V
		I _D = 250 μA, V _{GS} = 0 V	Q2	100			
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I _D = 250 μA, referenced to 25°C	Q1		80		mV/°C
		I _D = 250 μA, referenced to 25°C	Q2		80		
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 80 V, V _{GS} = 0 V	Q1			1	μA
		V _{DS} = 80 V, V _{GS} = 0 V	Q2			1	
I _{GSS}	Gate-to-Source Leakage Current, Forward	V _{GS} = ±20 V, V _{DS} = 0 V	Q1			±100	nA
		V _{GS} = ±20 V, V _{DS} = 0 V	Q2			±100	

NTTFD022N10C

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
ON CHARACTERISTICS							
V _{GS(th)}	Gate-to-Source Threshold Voltage	V _{GS} = V _{DS} , I _D = 44 μA	Q1	2	2.9	4	V
		V _{GS} = V _{DS} , I _D = 44 μA	Q2	2	2.9	4	
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate-to-Source Threshold Voltage Temperature Coefficient	I _D = 44 μA, referenced to 25°C	Q1		-9.2		mV/°C
		I _D = 44 μA, referenced to 25°C	Q2		-9.2		
r _{DS(on)}	Drain-to-Source On Resistance	V _{GS} = 10 V, I _D = 7.8 A	Q1		18.7	25	mΩ
		V _{GS} = 6 V, I _D = 3.9 A			28	61	
		V _{GS} = 10 V, I _D = 7.8 A, T _J = 125°C			32.6		
r _{DS(on)}	Drain-to-Source On Resistance	V _{GS} = 10 V, I _D = 7.8 A	Q2		18.7	25	mΩ
		V _{GS} = 6 V, I _D = 3.9 A			28	61	
		V _{GS} = 10 V, I _D = 7.8 A, T _J = 125°C			32.6		
g _{FS}	Forward Transconductance	V _{DS} = 5 V, I _D = 7.8 A	Q1		191		S
		V _{DS} = 5 V, I _D = 7.8 A	Q2		191		

DYNAMIC CHARACTERISTICS

C _{ISS}	Input Capacitance	Q1: V _{DS} = 50 V, V _{GS} = 0 V, f = 1 Mhz Q2: V _{DS} = 50 V, V _{GS} = 0 V, f = 1 MHz	Q1		585		pF
			Q2		585		
C _{OSS}	Output Capacitance		Q1		354		pF
			Q2		354		
C _{RSS}	Reverse Transfer Capacitance		Q1		8		pF
			Q2		8		
R _G	Gate Resistance	T _A = 25°C	Q1	0.1	1.5	3	Ω
			Q2	0.1	1.5	3	

SWITCHING CHARACTERISTICS

t _{d(ON)}	Turn-On Delay Time	Q1: V _{DD} = 50 V, I _D = 7.8 A, R _{GEN} = 6 Ω Q2: V _{DD} = 50 V, I _D = 7.8 A, R _{GEN} = 6 Ω	Q1		8.5		ns	
			Q2		8.5			
t _r	Rise Time		Q1		3.2		ns	
			Q2		3.2			
t _{d(OFF)}	Turn-Off Delay Time		Q1		13.3		ns	
			Q2		13.3			
t _f	Fall Time		Q1		4.1		ns	
			Q2		4.1			
Q _g	Total Gate Charge		V _{GS} = 0 V to 10 V	Q1		9.0		nC
				Q2		9.0		
Q _g	Total Gate Charge		V _{GS} = 0 V to 6 V	Q1		5.89		nC
				Q2		5.89		
Q _{gs}	Gate-to-Source Gate Charge	Q1: V _{DD} = 50 V, I _D = 7.8 A Q2: V _{DD} = 50 V, I _D = 7.8 A	Q1		2.67		nC	
			Q2		2.67			
Q _{gd}	Gate-to-Drain "Miller" Charge	Q1: V _{DD} = 50 V, I _D = 7.8 A Q2: V _{DD} = 50 V, I _D = 7.8 A	Q1		2.0		nC	
			Q2		2.0			

NTTFD022N10C


ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
DRAIN-SOURCE DIODE CHARACTERISTICS							
V_{SD}	Source-to-Drain Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 7.8\text{ A}$ (Note 2)	Q1		0.82	1.5	V
		$V_{GS} = 0\text{ V}, I_S = 7.8\text{ A}$ (Note 2)	Q2		0.82	1.5	
t_{rr}	Reverse Recovery Time	Q1: $I_F = 7.8\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$ Q2: $I_F = 7.8\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$	Q1		33		ns
			Q2		33		
Q_{rr}	Reverse Recovery Charge	$I_F = 7.8\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$	Q1		35		nC
			Q2		35		
t_{rr}	Reverse Recovery Time	Q1: $I_F = 7.8\text{ A}, di/dt = 1000\text{ A}/\mu\text{s}$ Q2: $I_F = 7.8\text{ A}, di/dt = 1000\text{ A}/\mu\text{s}$	Q1		14		ns
			Q2		14		
Q_{rr}	Reverse Recovery Charge	$I_F = 7.8\text{ A}, di/dt = 1000\text{ A}/\mu\text{s}$	Q1		91		nC
			Q2		91		


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:


- $R_{\theta JA}$ is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5 × 1.5 in. board of FR-4 material. $R_{\theta CA}$ is determined by the user's board design.




a) 70°C/W when mounted on a 1 in² pad of 2 oz copper.



b) 70°C/W when mounted on a 1 in² pad of 2 oz copper.



c) 135°C/W when mounted on a minimum pad of 2 oz copper.



d) 135°C/W when mounted on a minimum pad of 2 oz copper.

- Pulse Test: Pulse Width < 300 μs , Duty cycle < 2.0%.
- Q1: E_{AS} of 39 mJ is based on starting $T_J = 25^\circ\text{C}$; N-ch: $L = 3\text{ mH}, I_{AS} = 5.1\text{ A}, V_{DD} = 80\text{ V}, V_{GS} = 10\text{ V}$. 100% test at $L = 3\text{ mH}, I_{AS} = 5.3\text{ A}$.
Q2: E_{AS} of 39 mJ is based on starting $T_J = 25^\circ\text{C}$; N-ch: $L = 3\text{ mH}, I_{AS} = 5.1\text{ A}, V_{DD} = 80\text{ V}, V_{GS} = 10\text{ V}$. 100% test at $L = 3\text{ mH}, I_{AS} = 5.3\text{ A}$.
- Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

NTTFD022N10C

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Safe Operating Area




Figure 12. I_{PEAK} vs. Time in Avalanche

NTTFD022N10C

TYPICAL CHARACTERISTICS









Figure 13. Thermal Characteristics



WQFN12 3.3X3.3, 0.65P
CASE 510CJ
ISSUE O

DATE 31 MAR 2017



NOTES: UNLESS OTHERWISE SPECIFIED

- A) DRAWING DOES NOT FULLY CONFORM TO JEDEC REGISTRATION MO-220, VARIATION WEEC-1
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.

DOCUMENT NUMBER:	98AON13806G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	WQFN12 3.3X3.3, 0.65P	PAGE 1 OF 1

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:
Voice Mail: 1 800-282-9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative