

Housing - VC-MP-S1-2M6

1607732

<https://www.phoenixcontact.com/in/products/1607732>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Panel mounting base, Range of articles: VARIOCON, Housing, type: VC1, housing material: Zinc die-cast, surface bronzed and nickel-plated, color: gray

Housing - VC-MP-S1-2M6

1607732

<https://www.phoenixcontact.com/in/products/1607732>



Commercial Data

Item number	1607732
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	ABL
Product Key	ABLADB
GTIN	4017918952945
Weight per Piece (including packing)	361.1 g
Weight per Piece (excluding packing)	342 g
Customs tariff number	85369010
Country of origin	PL

Technical Data

Notes

Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

- The products are suitable for applications in plant, controller, and electrical device engineering.

- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.

- Assembled products may not be manipulated or improperly opened.

- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).

- When using the product in direct connection with third-party manufacturers, the user is responsible.

- For operating voltages > 50 V AC, conductive connector housings must be grounded

- Ensure that the protective or functional ground has been properly connected.

- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector

- Observe the corresponding technical data. You will find information:

- o On the product

- o On the packing label

- o In the supplied documentation

- o Online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) under the product

- Only use tools recommended by Phoenix Contact

- The installation notes/Design In documents online on the download page at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) must be observed for this product.

- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)

- Operate the connector only when it is fully plugged in.

- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the

Housing - VC-MP-S1-2M6



1607732

<https://www.phoenixcontact.com/in/products/1607732>

	standards.
	<ul style="list-style-type: none">• Observe the minimum bending radius of the cable. Lay the cable without twisting it.
	<ul style="list-style-type: none">• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Type	VC1
Product type	Panel mounting base

Dimensions

Width	78 mm
Height	50 mm
Length	36 mm

Material specifications

Color	gray
Color of the housing part	gray
Material	Zinc die-cast Powder coating (Housing)
Flammability rating according to UL 94	V0
Seal material	EPDM, conductive
O-ring material	NBR
Housing material	Zinc die-cast, surface bronzed and nickel-plated

Housing - VC-MP-S1-2M6

1607732

<https://www.phoenixcontact.com/in/products/1607732>



Approvals



EAC

Approval ID: B.01687

Housing - VC-MP-S1-2M6



1607732

<https://www.phoenixcontact.com/in/products/1607732>

Classifications

ECLASS

ECLASS-10.0.1	27440202
ECLASS-9.0	27440202
ECLASS-11.0	27440202

ETIM

ETIM 8.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Housing - VC-MP-S1-2M6

1607732

<https://www.phoenixcontact.com/in/products/1607732>



Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in