

Detailed information for: EF19-6.3

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)

[Print to Pdf...](#)

Data Sheet

Documentation

EF19-6.3

General Information

Extended Product Type:EF19-6.3

Product ID: 1SAX121001R1104

EAN: 4013614404016

Catalog Description: EF19-6.3 Electronic Overload Relay

Long Description: The EF19-0.32 is an self-supplied electronic overload relay, which means no extra external supply is needed. It offers reliable and fast protection for motors in the event of overload or phase failure. Easy to use like a thermal overload relay and compatible with standard motor applications, the electronic overload relay is convincing, above all, due to its wide setting range, high accuracy, high operational temperature range and the possibility to select a trip class (10E, 20E, 30E). Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and Test function and a trip indication. The overload relays are connected directly to the contactors. Single mounting kits are available as accessory. The EF19 and EF45 have ATEX and IECEx certification 1) 1) ATEX is valid for products produced from week 42, 2014. IECEx is valid for products produced from week 15, 2017.



Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Electronic Overload Relays

+ Accessories

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85364900

Dimensions

Product Net Width: 44.4 mm

Product Net Height: 85 mm

Product Net Depth: 59.3 mm

Product Net Weight: 0.158 kg

Popular Downloads

Data Sheet, Technical Information: [2CDC107025D0201](#)

Data Sheet, Technical Information (Part 2): [1SAX100509F0001](#)
[1SAX100510F0001](#)

Instructions and Manuals (Part 2): [2CDC107043M6801](#)

Dimension Diagram: [1SAX100403F0001](#)

Technical

Setting Range: 1.9 ... 6.3 A

Rated Operational Voltage: Auxiliary Circuit 600 V AC/DC
Main Circuit 690 V AC

Rated Operational Current (I_e): 6.3 A

Rated Operational Current AC-3 (I_e): 6.3 A

Rated Frequency (f): Auxiliary Circuit 50 Hz
Auxiliary Circuit 60 Hz
Auxiliary Circuit DC
Main Circuit 50 Hz
Main Circuit 60 Hz

Rated Impulse Withstand Voltage (U_{imp}): Auxiliary Circuit 6 kV
Main Circuit 6 kV

Rated Insulation Voltage (U_i): 690 V

Number of Poles: 3

Number of Auxiliary Contacts NC: 1

Number of Auxiliary Contacts NO: 1

Number of Protected Poles: 3

Conventional Free-air Thermal Current (I_{th}): Auxiliary Circuit NC 6 A
Auxiliary Circuit NO 6 A

Rated Operational Current AC-15 (I_e): (240 V) NC 3 A
(240 V) NO 3 A
(400 V) NC 1.1 A
(400 V) NO 1.1 A
(500 V) NC 0.75 A
(500 V) NO 0.75 A

Rated Operational Current DC-13 (I_e): (125 V) NC 0.55 A
(125 V) NO 0.5 A
(24 V) NC 1.5 A
(24 V) NO 1.5 A
(250 V) NC 0.27 A
(250 V) NO 0.27 A
(60 V) NC 0.55 A
(60 V) NO 0.55 A

Degree of Protection: IP20

Pollution Degree: 3

Connecting Capacity Auxiliary Circuit: Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible 1/2x 0.75 ... 2.5 mm²
Rigid 1/2x 1 ... 4 mm²

Connecting Capacity Main Circuit: Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible 1/2x 0.75 ... 2.5 mm²
Rigid 1/2x 1 ... 4 mm²

Tightening Torque: Auxiliary Circuit 0.8 ... 1.2 N·m
Main Circuit 0.8 ... 1.5 N·m

Wire Stripping Length:	Auxiliary Circuit 9 mm Main Circuit 9 mm
Recommended Screw Driver:	Auxiliary Circuit Pozidriv 2 Main Circuit Pozidriv 2
Mounting Position:	Position 1 to 6
Power Loss:	at Rated Operating Conditions per Pole 0.008 ... 0.083 W
Suitable For:	AF09 AF12 AF16 AF26
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C Operation Compensated -25 ... +70 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	Yes
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6:	3g / 3 ... 150 Hz
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Ampere Rating UL/CSA:	6.3 A
Contact Rating UL/CSA:	(NC:) B600 (NC:) Q600 (NO:) B600 (NO:) Q600
Connecting Capacity Main Circuit UL/CSA:	Flexible 1/2x 16-10 AWG Stranded 1/2x 16-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA:	Flexible 1/2x 18-10 AWG Stranded 1/2x 18-10 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 7 ... 1 in·lb Main Circuit 7 ... 13 in·lb

Certificates and Declarations (Document Number)

ABS Certificate:	1SAA941002-0101
ATEX Certificate:	1SAA941004-3901
BV Certificate:	1SAA941002-0201
CB Certificate:	1SAA964002-2002
CCC Certificate:	1SAA942001-3801
CCS Certificate:	1SAA941001-0901
cUL Certificate:	cUL_E48139
Declaration of Conformity - CE:	1SAD938513-0180

	1SAD938509-0180
DNV Certificate:	1SAA941003-0301
DNV GL Certificate:	1SAA941003-0302
EAC Certificate:	1SAA941003-2701
GOST Certificate:	1SAA941001-2701
Instructions and Manuals:	2CDC107023M6803
LR Certificate:	1SAA941002-0501
RINA Certificate:	RINA_ELE376813CS
RMRS Certificate:	1SAA964000-0703
RoHS Information:	1SAD938513-0180
UL Certificate:	UL_E48139

Container Information


Package Level 1 Units:	1 piece
Package Level 1 Width:	91 mm
Package Level 1 Height:	51.5 mm
Package Level 1 Length:	68 mm
Package Level 1 Gross Weight:	0.183 kg
Package Level 1 EAN:	4013614404016
Package Level 2 Units:	100 piece
Package Level 2 Width:	463 mm
Package Level 2 Height:	276 mm
Package Level 2 Length:	263 mm
Package Level 2 Gross Weight:	18.863 kg
Package Level 2 EAN:	4013614483295

Classifications

Object Classification Code:	F
E-nummer:	3224183
ETIM 4:	EC001080 - Electronic overload relay
ETIM 5:	EC001080 - Electronic overload relay
ETIM 6:	EC001080 - Electronic overload relay
eClass:	7.0 27371502
UNSPSC:	39121521

Contact information

What would you like to do?



Submit your inquiry

Your local ABB Sales Team

Country

Name

Name

Company

E-Mail

Phone

Zip code

Your message

[→ Privacy policy](#)

Cancel

Send message

▲ Close