


Soft feeling with metal contact provides low contact resistance.



Typical Specifications


Items	Specifications
Rating (max.)	50mA 16V DC
Rating (min.)	10 $\mu$ A 1V DC
Initial contact resistance	100m $\Omega$ max.
Travel (mm)	1.3

Product Line

Product No.	Operating force	Operating direction	Operating life (1mA 5V DC)	Minimum order unit (pcs.)	
				Japan	Export
SKPMAME010	1.57N	Toppush	100,000cycles	2,000	2,000
SKPMANE010	1.96N				
SKPMAPE010	2.45N				
SKPMBHE010	3N				

Packing Specifications

Taping



Number of packages (pcs.)			Tape width (mm)	Export package measurements (mm)
1 reel	1 case / Japan	1 case / export packing		
2,000	20,000	20,000	12	401 × 401 × 214

Note


For reels of 330mm diameter, please inquire.

Dimensions

Unit:mm

Style	PC board land dimensions (Viewed from switch mounting face)

Circuit Diagram



Detector

Push

Slide

Rotary

Encoders

Power

Dual-in-line Package Type

TACT Switch™

Sharp Feeling























Soft Feeling

Snap-in Type

Surface Mount Type

Radial Type

## List of Varieties

Type		Sharp Feeling Type			Soft Feeling Type							
		Radial			Snap-in			Surface Mount			Radial	
Series		SKRG	SKGK	SKRC	SKEG	SKEG	SKPF	SKPM	SKPG	SKPR	SKPL	SKPD
Detector												
Photo												
Features		Round terminal type	—	Round terminal type	—	—	High operation force and long travel	Low contact resistance	—	High operation force and Low contact resistance	Round terminal and low contact resistance	—
Water-proof		—	—	●	—	—	—	—	—	—	—	—
Dust-proof		—	—	●	—	—	—	—	—	—	—	—
Power	Toppush	●	●	●	●	—	●	●	●	●	●	●
	Sidepush	—	—	—	—	●	—	—	—	—	—	—
Dimensions (mm)	W	φ6.2	□6.6	φ9	□6	7.5	8	5.9	6.6	7.5	φ6.45	□7.8
	D					9.9	9	6	6.3	7.8		
	H					4.3	5	13	7	7.3		
Contact		—	—	—	Carbon			Silver	Carbon	Silver	Carbon	
Operation force coverage	~1N	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕
	1N~2N	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕
	2N~3N	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕
	3N~4N	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕	↕
Travel (mm)		0.25			1		※1	1.3		1	1.3	※1
Ground terminal		—	—	—	—	—	—	—	—	—	—	—
Operating temperature range		-40°C to +90°C	-20°C to +70°C	-40°C to +90°C	-20°C to +70°C			-40°C to +90°C				
Automotive use		●	—	—	—	—	●	●	●	●	●	●
Life Cycle												
Electrical performance	Rating (max.) (Resistive load)	50mA 12V DC			5mA 12V DC			50mA 16V DC	5mA 12V DC	50mA 16V DC		5mA 12V DC
	Rating (min.) (Resistive load)	10μA 1V DC			10μA 1V DC							
	Insulation resistance	100MΩ min. 100V DC for 1min.			100MΩ min. 100V DC for 1min.							
	Voltage proof	250V AC for 1min.			250V AC for 1min.							※2
Durability	Vibration	10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2hours respectively			10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2hours respectively							※3
	Lifetime	Shall be in accordance with individual specifications.			Shall be in accordance with individual specifications.							
Environmental performance	Cold	-40±2°C for 96h	-30±2°C for 96h	-40±2°C for 96h	-30±2°C for 96h		-40±2°C for 96h	-30±2°C for 96h		-40±2°C for 1000h	-40±2°C for 96h	
	Dry heat	90±2°C for 96h	80±2°C for 96h	90±2°C for 96h	80±2°C for 96h		90±2°C for 96h	80±2°C for 96h		90±2°C for 1000h	90±2°C for 96h	
	Damp heat	60±2°C, 90 to 95%RH for 96h		60±2°C, 90 to 95%RH for 1000h	60±2°C, 90 to 95%RH for 96h						60±2°C, 90 to 95%RH for 1000h	60±2°C, 90 to 95%RH for 96h
Page		277	278	279	280	280	282	283	284	285	286	287

W : Width. The most outer dimension excluding terminal portion.  
 D : Depth. The most outer dimension excluding terminal portion.  
 H : Height. The minimum dimension if there are variances.

- TACT Switch™ Soldering Conditions . . . . . 288
- TACT Switch™ Cautions . . . . . 289

### Notes

1. The automotive operating temperature range to be individually discussed upon request.
2. ● indicates applicability to all products in the series.
3. ※ 1 See the relevant pages for respective product descriptions
4. ※ 2 50MΩ min. 100V DC for 1min. SKPDAF:100MΩmin. 100V DC for 1min.
5. ※ 3 100V AC for 1min.SKPDAF:250V DC for 1min.


# TACT Switch™ Soldering Conditions

## Condition for Reflow

Available for Surface Mount Type.

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple 0.1 to 0.2 φ CA (K) or CC (T) at solder joints (copper foil surface).  
A heat resistive tape should be used to fix thermocouple.

3. Temperature profile



## Notes

1. The above temperature shall be measured of the top of switch. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the material, size, thickness of PC boards and others. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

## Conditions for Auto-dip

Available for Snap-in Type and Radial Type

Items	Condition
<b>Flux built-up</b>	Mounting surface should not be exposed to flux
<b>Preheating temperature</b>	Ambient temperature of the soldered surface of PC board. 100°C max.
<b>Preheating time</b>	60s max.
<b>Soldering temperature</b>	260°C max.
<b>Duration of immersion</b>	5s max.
<b>Number of soldering</b>	2times max.

SKHH、SKPD Series

Items	Condition
<b>Flux built-up</b>	Mounting surface should not be exposed to flux
<b>Preheating temperature</b>	Ambient temperature of the soldered surface of PC board. 110°C max.
<b>Preheating time</b>	60s max.
<b>Soldering temperature</b>	260°C max.
<b>Duration of immersion</b>	5s max.
<b>Number of soldering</b>	2times max.

SKQJ、SKQK、SKEG Series

Items	Condition
<b>Flux built-up</b>	Mounting surface should not be exposed to flux
<b>Preheating temperature</b>	Ambient temperature of the soldered surface of PC board. 100°C max.
<b>Preheating time</b>	45s max.
<b>Soldering temperature</b>	255°C max.
<b>Duration of immersion</b>	5s max.
<b>Number of soldering</b>	2times max.

## Notes

1. Consult with us for availability of TACT Switch™ washing.
2. Prevent flux penetration from the top side of the TACT Switch™.
3. Switch terminals and a PC board should not be coated with flux prior to soldering.
4. The second soldering should be done after the switch is stable with normal temperature.
5. Use the flux with a specific gravity of min 0.81.  
(EC-19S-8 by TAMURA Corporation, or equivalents.)

## Manual Soldering (Except SKRT Series)

Items	Condition
<b>Soldering temperature</b>	350°C max.
<b>Duration of soldering</b>	3s max.
<b>Capacity of soldering iron</b>	60W max.

SKHH、SKHW、SKRG、SKPD Series

Items	Condition
<b>Soldering temperature</b>	360°C max.
<b>Duration of soldering</b>	3s max.
<b>Capacity of soldering iron</b>	60W max.

SKQJ、SKQK、SKEG Series

Items	Condition
<b>Soldering temperature</b>	350°C max.
<b>Duration of soldering</b>	3s max.
<b>Capacity of soldering iron</b>	20W max.

Detector  
Push  
Slide  
Rotary  
Encoders  
Power  
Dual-in-line  
Package Type

TACT Switch™

Sharp  
Feeling  
Soft  
Feeling  
Snap-in  
Type  
Surface  
Mount Type  
Radial  
Type