

8080 -1G1 -LF Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



8080 -1G1 -LF

[Active](#)

Transistor Sockets and Adapters

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Socket
- ? Terminal Style = Solder
- ? Terminal Type = Contact
- ? Lead Size Accepted = 1.02 mm
- ? 3 Terminals

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [TRANSISTOR SOCKET](#) (PDF, English)
onlinecomponents.com
THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Socket
- ? Terminal Type = Contact
- ? Product Series = 8080 -1G Series

Electrical Characteristics:

- ? Number of Solder Lugs = 2

Termination Related Features:

- ? Terminal Plating = Tin

Body Related Features:

- ? Terminal Style = Solder
- ? Number of Terminals = 3
- ? Socket Type = TO -3
- ? Terminal Material = Beryllium Copper
- ? Insulator Material = Phenolic

Configuration Related Features:

- ? Lead Size Accepted (mm [in]) = 1.02 [0.040]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Operating Temperature (°C) = -55 - +125

Other:

- ? Brand = AMP