

5749232 - 1 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



5749232 - 1

[Active](#)

Shielded Miniature Circular DIN Connectors

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Connector
- ? Number of Positions = 8
- ? PCB Mount Angle = Right Angle
- ? Shielded
- ? Without Front Panel Grounding

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [RECEPTACLE ASSY W/ HOLD DOWN, 8 POS. RIGHT ANGLE, MI...](#)
(PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Connector
- ? [Number of Positions](#) = 8
- ? [Shielded](#) = Yes
- ? [PCB Mount Angle](#) = Right Angle
- ? [Front Panel Grounding](#) = Without
- ? [PCB Retention Feature](#) = Yes
- ? [Gender](#) = Receptacle
- ? [Stacked](#) = No
- ? [Color Code](#) = None
- ? PCB Mount Style = Thru Hole
- ? Shield Material = Copper Alloy
- ? Comment = Recommended PC board thickness is 1.6 mm.

Termination Related Features:

- ? [Grounding Clips](#) = Without
- ? Solder Tail Contact Plating = Tin

Body Related Features:

- ? PCB Retention Method = Hold Down Post
- ? Shield Plating = Bright Tin

Contact Related Features:

- ? [Contact Mating Area Plating Material](#) = Gold Flash
- ? Contact Material = Copper Alloy
- ? Contact Underplating = Nickel (50)

Housing Related Features:

- ? Housing Material = Thermoplastic
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Color = Black

Configuration Related Features:

- ? SPDIF Connector = Without

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- ? Packaging Quantity = 37

Other:

- ? Brand = AMP