



What can we help you find?

🧮 My Cart | 🕒 My Part Lists | Sign In/Register - 🐔 English (Change)



Email

Products Industries About TE Support Center Resources My Account

Home > Products > Switches & Knobs > Product Feature Selector > Product Details

UP01DTBNLA04 Product Details



UP01DTBNLA04

Snap Action Switches



Product Highlights:

- Switch Style = Ultra Miniature
- Actuator Style = Lever, Normal
- Termination Type = Printed Circuit Board Left
- Single Pole Double Throw Configuration (Pole-Throw)
- Contact Rating = 0.1A

View all Features














Ouick Links

📴 Share

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector ▶ Contact Us About This Product

🗎 Print





Documentation & Additional Information

Product Drawings:

SWITCH, SNAP ACTION, ULTRAMINIATURE (PDF, English)

Catalog Pages/Data Sheets:

SWITCHES CORE PROGRAM CATALOG (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version B1)
- 3D Model (IGES, Version B1)
- 3D Model (STEP, Version B1)

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Actuator Style = Lever, Normal
- Termination Type = Printed Circuit Board Left
- Configuration (Pole-Throw) = Single Pole Double Throw
- Mount Angle = Right Angle

Mechanical Attachment:

Operating Force (g [oz]) = 50 [1.764]

Electrical Characteristics:

Contact Rating = 0.1A

Body Features:

- Switch Style = Ultra Miniature
- Releasing Force (g [oz]) = 8 [0.282]
- Pre Travel (mm [in]) = 3.00 [0.118]
- Operating Position (mm [in]) = 7.90 [0.311]
- Over Travel (mm [in]) = 0.60 [0.024] Movement Differential (mm [in]) = 0.80 [0.031]

- Contact Features:
 - Contact Base Material = Brass
 - Contact Plating = Gold over Nickel

Housing Features:

Housing Material = Nylon

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

Brand = Tyco Electronics

Corporate Information

Who We Are

News Room

Quick Links Check Distributor Inventory

Cross Reference Investors

Supplier Portal Product Compliance Support Center

Careers Site Map

Find Documents & Drawings

Customer Support Email or Chat With Us Find a Phone Number Search Knowledge Base Manage your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address











