ZONE	REV.	REVISION DESCRIPTION	ECN NO.	DATE
	.	.	.	.





COLOR	SOCKET	WIRE GAGE
WHT/BLK	A	AWG 26
WHT/BRN	B	
WHT/RED	C	
WHT/ORN	D	
WHT/YEL	E	
WHT/GRN	F	
WHT/BLU	G	
WHT/VIO	H	
WHT/GRY	J	
WHT	K	
GRY/BLK	L	
GRY/BRN	M	
GRY/RED	N	
GRY/ORN	P	
ORANGE	R	
GREEN	S	
BLACK	T	AWG 22
YELLOW	U	AWG 26
RED	V	AWG 22

PART NO.	CABLE LENGTH +5%/-0
31219-1410	10FT
31219-1420	20 FT
31219-1430	30 FT
31219-1450	50 FT

NOTES (UNLESS OTHERWISE INDICATED):

1. MAT'L: MS3116J14-19S
   37063 CABLE (PVC JACKET)
   BLACK POLYURETHANE OVERMOLD
2. OPERATING TEMP -40 TO +80°C
3. STANDARD BEI (SENSATA) PINOUT/WIRE COLOR

APPLICATION NOTES;
1. FOR USE WITH ABSOLUTE ENCODERS WITH GRAY CODE OR NATURAL BINARY PARALLEL OUTPUTS
2. SHIELD DRAIN IS NOT CONNECTED AT CONNECTOR. SHIELD CONNECTION MAY BE REQUIRED AT CONTROLLER END FOR SAFETY AND NOISE IMMUNITY.

UNCONTROLLED COPY

FIRST ISSUE DATE: 05/07/19
DRAWN: DRC
APPROVED: MFB
DATE: 05/06/19
ECN:
DATE:
MATERIAL: NOTED

SENSATA TECHNOLOGIES PROPRIETARY AND CONFIDENTIAL. NEITHER THIS PRINT NOR THE INFORMATION CONTAINED HEREON IS TO BE USED AGAINST THE INTERESTS OF SENSATA TECHNOLOGIES OR AGAINST THE INTERESTS OF ANY OF ITS AFFILIATED COMPANIES OR WHOLLY OWNED SUBSIDIARIES.

INTERPRET DIMENSIONING AND TOLERANCING PER ASME Y14.5-2009. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES[MILLIMETERS] AND ARE INTENDED AS NOMINAL SEE PRODUCT SPECIFICATIONS FOR MORE DETAILS.

DO NOT SCALE DRAWING

THIRD ANGLE PROJECTION

Sensata Technologies
BEI SENSORS
1461 LAWRENCE DRIVE
THOUSAND OAKS, CA 93120

TITLE
M14/19 CONNECTOR AND CABLE ASSEMBLY, ABSOLUTE PARALLEL OUTPUTS

SIZE	DWG NO.	REV.
B	09911-005	.

SCALE 1:2 | SOLIDWORKS | SHEET 1 OF 1

DEVICE:

PROJECT: