



Product: [9L28034](#)

Flat Gray Ribbon Cable 9L280 Series, #28-34c, .050" Pitch

Product Description

Belden .050" pitch gray ribbon cable was designed for general purpose electronic interconnect applications. The cable provides reliable mass-termination to standard IDC connectors.

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Material | Construction n x D | No. of Conductors |
|-----|--------------------|--------------------|-------------------|
| 28 | TC - Tinned Copper | Stranded | 34 |

| | |
|------------------|----|
| Conductor Count: | 34 |
|------------------|----|

Insulation

| Material | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.01 in |

Color Chart

| Number | Color |
|--------|-------|
| | Gray |
| 3 | |

Outer Shield Material

| Material |
|-----------|
| No Shield |

Outer Jacket Material

| Nominal Wall Thickness |
|------------------------|
| 0.035 in |

Construction and Dimensions

| | |
|-------------------------------------|---------|
| Cond Spacing Center-Center: | .050 in |
| Cond Spacing Center-Center Outside: | 1.65 in |
| OuterJacket1, Nominal Width: | 1.70 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR |
|-----------------------|
| 68.2 Ohm/1000ft |

Capacitance

| Element | Nom. Capacitance Conductor to Conductor |
|---------------|---|
| @ 1 kHz (GSG) | 18 pF/ft |
| @ 1 MHz (GS) | 10 pF/ft |
| @ 1 MHz (GSG) | 15 pF/ft |

Inductance

| Element | Nominal Inductance |
|---------------|--------------------|
| @ 1 MHz (GS) | 0.29 μ H/ft |
| @ 1 MHz (GSG) | 0.2 μ H/ft |

Impedance

| Nominal Characteristic Impedance | Nominal Characteristic Impedance Description |
|----------------------------------|--|
| 150 Ohm | (GS) |
| 105 Ohm | (GSG) |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 10 MHz | 2.8 dB/100ft |
| 20 MHz | 4.8 dB/100ft |
| 30 MHz | 6.5 dB/100ft |
| 40 MHz | 8.3 dB/100ft |
| 50 MHz | 9.8 dB/100ft |
| 60 MHz | 12 dB/100ft |
| 70 MHz | 13 dB/100ft |
| 80 MHz | 14 dB/100ft |
| 90 MHz | 15.8 dB/100ft |
| 100 MHz | 17 dB/100ft |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.4 ns/ft | 72% |

Unbalanced Crosstalk

| Element | Typical Unbalanced NEXT % | Typical Unbalanced FEXT % | Typical Cross Talk Pulse Rise Time (ns) |
|----------------------|---------------------------|---------------------------|---|
| 10 ft. sample length | 4.8 MHz | 7 MHz | 3 ns |
| 10 ft. sample length | 3.5 MHz | 4.7 MHz | 5 ns |
| 10 ft. sample length | 3 MHz | 3 MHz | 7 ns |

High Freq

| Frequency [MHz] |
|-----------------|
| 10 MHz |
| 20 MHz |
| 30 MHz |
| 40 MHz |
| 50 MHz |
| 60 MHz |
| 70 MHz |
| 80 MHz |
| 90 MHz |
| 100 MHz |

Current

| Max. Recommended Current [A] |
|------------------------------|
| 1 Amp per Conductor at 20°C |

Voltage

| Dielectric Withstand Voltage | UL Voltage Rating |
|------------------------------|-------------------|
| 2,000 V RMS | 300 V RMS |

Temperature Range

| | |
|-----------------------|-----------------|
| Operating Temp Range: | -40°C To +105°C |
|-----------------------|-----------------|

Mechanical Characteristics

| | |
|-----------------------------|---------------|
| Bulk Cable Weight: | 39 lbs/1000ft |
| Min Bend Radius/Minor Axis: | 3 in |

Standards

| | |
|--------------------------|------------------------|
| UL Rating: | 105°C, 300 V RMS, VW-1 |
| UL AWM Style Compliance: | 2651 |
| CSA Rating: | 105°C, 300 V RMS, FT1 |
| CSA AWM Compliance: | I A 105°C 300V FT1 |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-07-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|-----------|
| UL Flammability: | VW-1 |
| CSA Flammability: | FT1 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Length | UPC |
|-----------------|-------|--------|--------------|
| 9L28034 008H100 | Gray | 100 ft | 612825221685 |

Product Notes

| | |
|--------|--|
| Notes: | GS=Ground-Signal Mode; GSG=Ground-Signal-Ground Mode |
|--------|--|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.298 Revision Date: 06-24-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.