MINISMDC075F-2 Product Details

Share   Print   Email

MINISMDC075F-2

TE Internal Number: RF1404-000

✔ Active

PolySwitch Resettable Devices

🍃 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:
- Surface Mount Application
- Vmax = 13.2 V
- Imax = 100 A
- Family Name = miniSMD
- Surface Mount Construction

View all Features

Quick Links
- ▸ Check Pricing & Availability
- ▸ Search for Tooling
- ▸ Product Feature Selector
- ▸ Contact Us About This Product

Add to My Part List   Request Sample   Find Similar Products   Buy Product

Documentation & Additional Information

Product Drawings:
- None Available

Catalog Pages/Data Sheets:
- CP CATALOG 2011 - SURFACE-MOUNT (PDF, English)

Product Specifications:
- miniSMDC075F (PDF, English)

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

Related Products:
- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- UL File Number = E74889
- CSA File Number = CA78165

Electrical Characteristics:
- Vmax (V) = 13.2
- Imax (A) = 100
- IH (Room Temperature) (A) = 0.75
- IT (Room Temperature) (A) = 1.50
- Rmin (Ω) = 0.11
- R1 Max [Post Trip] (Ω) = 0.45

Termination Features:
- Construction = Surface Mount

Contact Features:
- Family Name = miniSMD

Configuration Features:
- Form Factor (inches) = 1812
- Form Factor (mm) = 4532

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72111045

Environmental:
- Operating Temperature (Max.) (°C) = 85

Operation/Application:
- Application = Surface Mount

Packaging Features:
- Packaging Method = Tape & Reel

Other:
- Brand = Raychem