

CHARACTERISTICS

Weight: 0,725 Kg / 1,6 Lb
 Housing in ZAMAK
 Impeller in plastic UL 94 V-0
 L-10 life expectancy at 40°C: 80.000 hours
 Operating temperature range: -10 / +55 °C
 Storage temperature: -40 / +70°C
 Connection: Terminals
 Impedance Protected



OPTIONS

- Speed sensor
- Other IP levels
- Flying leads connection
- Salt spray protection
- Shocks and vibrations protection
- Marine application
- Wide temperature range
- Other voltages

Part Number	Voltage V	Frequency Hz	Nb Phases	Airflow		Pressure		Nominal speed RPM	Noise level LP dBA	Nominal current mA	Starting current mA	power W	Capacitor µF
				l/s	CFM	mm H ₂ O	inch H ₂ O						
141LV0281010	115	50	1	23,5	49,82	1,9	0,07	1600	27,5	110	125	9	
	82	60	1	26,0	55,12	1,9	0,07	1700	28	100	110	8	
82	220	50	1	23,5	49,82	1,9	0,07	1600	27,5	60	70	10	
	81	60	1	26,0	55,12	1,9	0,07	1700	28	55	65	9	
141LT0282010	115	50	1	33,0	69,96	4	0,16	2200	35	125	160	10	
	82	60	1	35,0	74,20	3,6	0,14	2400	38,5	110	140	9	
81	220	50	1	33,0	69,96	4	0,16	2200	35	75	90	12	
	81	60	1	35,0	74,20	3,6	0,14	2400	38,5	65	75	10	
141LS0282010	115	50	1	42,0	89,04	8,5	0,33	2800	44,5	160	275	13	
	82	60	1	48,0	101,76	9,5	0,37	3200	49,5	140	240	12	
81	220	50	1	42,0	89,04	8,5	0,33	2800	44,5	95	150	14	
	81	60	1	48,0	101,76	9,5	0,37	3200	49,5	80	130	12	

