

CHARACTERISTICS

Weight: 0,725 Kg / 1,6 Lb
 Housing in ZAMAK
 Impeller in plastic UL 94 V-0
 L-10 life expectancy at 40°C: 80.000 hours
 Operating temperature range: -10 / +70 °C
 Storage temperature: -40 / +70°C
 Connection: Terminals
 Impedance Protected



OPTIONS

Speed sensor
 Other IP levels
 Flying leads connection
 Salt spray protection
 Shocks and vibrations protection
 Marine application
 Wide temperature range
 Other voltages

Part Number	Voltage		Frequency	Nb Phases	Airflow		Pressure		Nominal speed	Noise level LP	Nominal current	Starting current	power	Capacitor
	V	Hz			l/s	CFM	mm H ₂ o	inch H ₂ o						
129XL0282010	115	50	1	21,5	45,58	1,4	0,06	1350	31	135	145	12		
	82	115	60	1	24,5	51,94	1,7	0,07	1550	33,5	115	125	10	
	81	220	50	1	21,5	45,58	1,4	0,06	1350	31	75	90	12	
129LG0282010	115	50	1	34,0	72,08	4	0,16	2200	44,5	200	250	16		
	82	115	60	1	39,0	82,68	4,3	0,17	2400	47,5	160	200	13	
	81	220	50	1	34,0	72,08	4	0,16	2200	44,5	110	140	18	
129XR0282010	115	50	1	45,0	95,40	8,5	0,33	2800	49	200	310	16		
	82	115	60	1	52,0	110,24	10	0,39	3200	54	180	260	15	
	81	220	50	1	45,0	95,40	8,5	0,33	2800	49	125	170	18	
81	220	60	1	52,0	110,24	10	0,39	3200	54	105	150	15		

