Fair-Rite Products Corp.

Your Signal Solution®

Round Cable Snap- Its (0475164181)



Flat Cable Cores

Part Number: 0475164181

75 ROUND CABLE CORE ASSEMBLY

Explanation of Part Numbers: – Digits 1 & 2 = Product Class

– Digits 3 & 4 = Material Grade

Round cable snap- its can easily accommodate round cables or bundled wires with diameters from 2.5 mm (0.100) to 25.4 mm (1.000). These assemblies are available in four ferrite material classes to suppress differential or common- mode conducted EMI from 1 MHz into the GHz region. The polypropylene cases are meeting the RoHS restrictions of hazardous substances and have a flammability rating of UL 94 V-0.

Many of the snap- it parts have round core equivalents. See Round Cable EMI Suppression Cores.


Round Cable Snap- It Kits are available for each of the four suppression materials. 31 Snap- It Kit (0199000030), 43 Snap- It Kit (0199000031), 46 Core and Snap- It Kit (0199000032) and 61 Snap- It Kit (0199000033).

Catalog Drawing 3D Model

The B dimension is the core inside diameter.

Weight: 61 (g)

Dim	mm	mm tol	nominal inch	inch misc.	Cable Inform	Cable Information				
А	30	+/- 1.5 1.181	1.181		Max	Max	Solid			
В	12.75	0.502	0.502		Diameter	Dimension	Equivalent			
С	39.5	+/- 2.0 1.555	1.555		12.7		2675102002			
D	15.5	+/75 0.610	0.61		12.75 0.502	_				




Typical Impedan	$ce(\Omega)$
200 kHz	19
500 kHz^+	55
1 MHz^+	91
2 MHz	69
5 MHz^{+}	53

Round cable snap- it assemblies are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is listed on our catalog drawing.

Catalog Drawing

Single turn impedance tests for 31, 43 and 46 material cores are performed on the E4991A/HP4291B Impedance Analyzer. The 61 material parts are tested on the E4991A / HP4291B Impedance Analyzer and 75 material parts are tested on the E4990A Impedance Analyzer. Cores are tested with the shortest practical wire length.



	Fair- Rite Products Corp.			One Commercial Row, Wallkill, New York 12589-0288				
888-324-7748		845-895-2055		Fax: 845-895-2629		ferrites@fair- rite.com		www.fair- rite.com