

## Cord Connectors

### Straight Male

Form Size 5-8



Cast Aluminum

Cast Aluminum  
Malleable Iron

UL Listed to Type 4, 4X, 12 and Type 13



**IP66\***  
SUITABILITY

N.P.T. Hub Size	Cord Dia. Inches	(mm)	Form Size	Cast Aluminum	Malleable Iron†
1"	.88"-1.00"	(22.2-25.4)	F5	<b>SHC1046</b>	•
	1.00"-1.13"	(25.4-28.6)		<b>SHC1047**</b>	•
	1.13"-1.25"	(28.6-31.7)		<b>SHC1048**</b>	•
	1.25"-1.38"	(31.7-34.9)		<b>SHC1049**</b>	•
1 1/4"	.75"-.88"	(19.0-22.2)	F5	<b>SHC1050</b>	•
	.88"-1.00"	(22.2-25.4)		<b>SHC1051</b>	•
	1.00"-1.13"	(25.4-28.6)		<b>SHC1052</b>	<b>SHC1052ZP</b>
	1.13"-1.25"	(28.6-31.7)		<b>SHC1053</b>	<b>SHC1053ZP</b>
1 1/2"	1.25"-1.38"	(31.7-34.9)	F5	<b>SHC1054**</b>	<b>SHC1054ZP</b>
	.75"-.88"	(19.0-22.2)		<b>SHC1055</b>	•
	.88"-1.00"	(22.2-25.4)		<b>SHC1056</b>	•
	1.00"-1.13"	(25.4-28.6)		<b>SHC1057</b>	<b>SHC1057ZP</b>
1 1/2"	1.13"-1.25"	(28.6-31.7)	F5	<b>SHC1058</b>	<b>SHC1058ZP</b>
	1.25"-1.38"	(31.7-34.9)		<b>SHC1059</b>	<b>SHC1059ZP</b>
	1.38"-1.50"	(34.9-38.1)		<b>SHC1061</b>	•
	1.50"-1.63"	(38.1-41.3)		<b>SHC1062**</b>	•
2"	1.63"-1.75"	(41.3-44.4)	F6	<b>SHC1063**</b>	•
	1.75"-1.88"	(44.4-47.6)		<b>SHC1064**</b>	•
	1.25"-1.38"	(31.7-34.9)		<b>SHC1065</b>	•
	1.38"-1.50"	(34.9-38.1)		<b>SHC1066</b>	•
2"	1.50"-1.63"	(38.1-41.3)	F6	<b>SHC1067</b>	•
	1.63"-1.75"	(41.3-44.4)		<b>SHC1068</b>	•
	1.75"-1.88"	(44.4-47.6)		<b>SHC1069</b>	•
	1.69"-1.81"	(42.9-46.0)		<b>SHC1070</b>	•
2"	1.81"-1.94"	(46.0-49.2)	F7	<b>SHC1071</b>	•
	1.94"-2.06"	(49.2-52.4)		<b>SHC1072**</b>	•
	2.06"-2.19"	(52.4-55.6)		<b>SHC1073**</b>	•
	2.19"-2.31"	(55.6-58.7)		<b>SHC1074**</b>	•
2 1/2"	2.19"-2.31"	(55.6-58.7)	F7	<b>SHC1076</b>	•
	2.31"-2.44"	(58.7-61.9)		<b>SHC1077</b>	•
	1.69"-1.81"	(42.9-46.0)		<b>SHC1078</b>	•
	1.81"-1.94"	(46.0-49.2)		<b>SHC1079</b>	•
3"	1.94"-2.06"	(49.2-52.4)	F7	<b>SHC1080</b>	•
	2.06"-2.19"	(52.4-55.6)		<b>SHC1081**</b>	•
	2.19"-2.31"	(55.6-58.7)		<b>SHC1086</b>	•
	2.31"-2.44"	(58.7-61.9)		<b>SHC1087</b>	•
3"	2.44"-2.63"	(61.9-66.7)	F8	<b>SHC1088</b>	•
	2.63"-2.81"	(66.7-71.4)		<b>SHC1089</b>	•
	2.81"-3.00"	(71.4-76.2)		<b>SHC1090</b>	•
	3.00"-3.25"	(76.2-82.5)		<b>SHC1091</b>	•
3"	2.44"-2.63"	(61.9-66.7)	F8	<b>SHC1092</b>	•
	2.63"-2.81"	(66.7-71.4)		<b>SHC1093</b>	•
	2.81"-3.00"	(71.4-76.2)		<b>SHC1094</b>	•
3"	3.00"-3.25"	(76.2-82.5)	F8	<b>SHC1095**</b>	•

Note: See pages T-87 to T-98 for additional technical data and dimensional drawings.

\*IP66 Suitability when used with optional metal clad O-ring shown on page T-83.

\*\*Cable jacket may have to be stripped to pass through connector body.

F5 and larger will not be color coded.