

HBL7468 -- Twist-Lock Receptacle



2P2W, 15A 125V, ML-1R, Stainless Flange

Product Specifications

Product Type



Product Item	Flanged Receptacle
Wiring Scheme	2-Pole, 2-Wire Non-Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	ML-1R
Item Style	Standard
Device Color	Black
Terminal Screw Material	Brass
Body Contact Carrier Material	Black Thermoset
Contact Spring Material	.032" (.8) Bronze
Flanged Casing Material	.025" Stainless Steel
Mounting Screw Material	Brass, Nickel plated
Ground Contact Material	.032" Bronze
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors.
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
UPC Number	783585237336
Weight in LBs	0.05
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

