



SD

NOTES:

- FOR USE WITH RG-55, 58, 223/U CABLE.
- FOR CABLING INSTRUCTIONS USE CP-1025.
- MATERIALS:
 INSULATOR: TEFLON, ASTM-D-4894
 C-RING } PHOSPHORUS BRONZE, ASTM-B-103
 OUTER CONTACT
 GASKETS: SILICONE RUBBER, A-A-59588
 WASHER: BRASS, ASTM-B-36
 ALL OTHER METAL PARTS: BRASS, ASTM-B-16
- FINISHES:
 ALL METAL PARTS: SILVER PLATED, ASTM-B-700
- ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 WORKING VOLTAGE: 1000 VOLTS RMS
 FREQUENCY RANGE: DC TO 11 GHz.

MAY 2007 THIS DRAWING BECAME THE PROPERTY OF PROPERTY OF WINCHESTER ELECTRONICS CORPORATION, WALLINGFORD, CT 06492

SD

KN-59-06

REVISIONS

ISSUE	CHANGES
8	CN 38979 C REDRAWN JPK 12/08/03
9	CN 39703 E BAM 11/15/06
10	CN 39707 C PMC 11/20/06

KN-59-06SD

SCALE 2 : 1

APPROX SURFACE AREA

USED ON

REF:

N ANGLE PLUG

DRAWN J. KENNEDY	DATE 12/09/03
DESIGN	DATE
APPR.	DATE

KINGS
ELECTRONICS CO., INC.
ROCK HILL, SOUTH CAROLINA 29730

KN-59-06