

Solutions for Electronic Specialty Markets (ESM)

Product Catalog for Electronic Specialty Markets

- 3M Electronic Specialty Markets New Product Releases
- 3M Abrasives
- 3M Adhesives, Cleaners & Compounds
- 3M Breadboards & Test Clips
- 3M Cable & Assemblies
- 3M Copper Interconnects
- 3M Fiber Optics
- 3M Fire Protection
- 3M Heat Shrink
- 3M Identification Systems
- 3M Occupational Health & Safety Products
- 3M Protective Bumpers
- 3M Reclosable Fasteners
- 3M Splicing, Terminating & Ducting
- 3M Static Control**
- 3M Tapes
- 3M Terminals, Kits & Tools
- 3M Vacuums & Accessories
- 3M Warehousing & Packaging Supplies
- 3M Wire Connectors

Other Tools

- What's New
- Sales Contacts
- U.S. Distributors


Search This Product Catalog

By Keyword

- [Product Catalog for Electronic Specialty Markets](#)
- [3M Static Control](#)
- [Bags, Films & Foams](#)
- [Metal - In Static Shielding Bags 1900](#)

3M Static Control Metal-In Static Shielding Bags, 1900 18X18

[Printer-friendly format](#)



3M Static Control Metal - In Static Shielding Bag 1900 is an economical alternative shielding bag for less demanding applications where testing and reusing bags are not prime considerations.

[\[click to enlarge\]](#)

3M Id : 98 - 0798 - 4484 - 5
GTIN(UPC/EAN) : 0 00 51138 74799 2

Additional Information

Aluminum is vapor - coated on half - mil polyester. This shielding layer is bonded between the polyester layer and a static - dissipative polyethylene inner layer. The bags are amine - free, non - corrosive and meet EIA - 541 definition for static shielding/dissipati

Learn More . . .

- [Packaging Data](#)
- [3M Static Control Products Overview - Brochure \(PDF 381.5 K\)](#)
- [3M Static Control Static Shielding Bag SCC 1000 - Data Sheet \(PDF 841.3 K\)](#)

Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.

Characteristics

Amine Free	Yes
Biodegradable	No
Coating	Aluminum w/Vapor
Color	Silver
Conductive	No
Cushioned	No
Custom Printing	Yes
Disposable	Yes
Dissipative	Yes
Non-Corrosive	Yes
Shelf Life	12 Month
Static Shielding	Metal In
Thickness	2.9 Milli-inch (Mil)
Volume Conductive	No