



Home > Products > Key Operated Interlock > GKN > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## GKNA21



Actual product appearance may vary.

**GKN Series, Key Operated Safety Interlock Switch, 2NC/1NO Direct Opening, Slow Action, NPT Conduit, Plastic Housing, Silver Contacts**

### Features

Positive opening safety contacts  
 Choice of six actuators  
 Double insulated per IEC 60947-1  
 Global approvals (cULus, CE, CCC)  
 Three cable entries  
 Large wiring cavity  
 Large M20 cable entry  
 Four-entry head

### Potential Applications

Woodworking machinery  
 Printing/paper finishing equipment  
 Plastic molding equipment  
 Printing machinery  
 Bailing and pumping equipment  
 Semiconductor manufacturing equipment  
 Packaging wrapping  
 Specialty equipment

### Description

The GKN Series safety interlock switches provide superior reliability in a compact, cost-effective package size. Six different types of actuator keys are available. The GKN Series conforms to IEC 60947-1 and carries cULus, CE, and CCC approvals.

### Supporting Documentation

- ▶ [Installation Instructions](#)
- ▶ [Accessories](#)

Product Specifications	
Product Type	Key Operated Safety Interlock Switch
Actuator	Key
Switch Type	2NC/1NO Direct Opening, Slow Action
Contact Material	Silver
Termination Type	1/2 NPT
Ampere Rating	100 mA to 10 A (Thermal)
Voltage	240 Vac and 250 Vdc Maximum
Housing Material	Plastic
Series Name	GKN
Shock	50 g per IEC 68 -2-27
Vibration	10 g per IEC 68 -2-6
Sealing	IP67, NEMA 1, 4, 12, 13, IP67, NEMA 1, 4, 12, 13
Approvals	cULus, CE, CCC
CSA File #	E37138
UL File #	E37138
Agency Approvals and Standards	IEC 947 -5-1, EN 60947 -5-1, UL508, CSA C 22.2 No.14
Mechanical Life	1 Million,,1 Million,
Operating Temperature Range	-25 °C to 85 °C [ -13 °F to 185 °F]
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Note 1	Low Voltage Directive 73/23/EEC, as amended by directive 93/68/EEC. Machinery Directive 98/37/EEC only as the directives relate to the components being used in a safety function.

### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

Specification Search