Honey	well			→ He	oneywell.com	Automation & Con	trol Solution
HOME	ABOUT US	KEY INDUSTRIES SERVED	PRODUCTS & INFORMATION	NEWS & EVENTS	SALES & S	UPPORT	LOGIN
Honeywell	Sensing and	l Control					
Search 🤤		SSCMAND010BG2A5 (Home: Products: Sensors » Silicon Pressure Sensors » Low Pressure Sensors » TruStability® SSC)				conta	
narrow your search Products Controls Monitoring and Lighting (286) Machine Safety (1727) Sensors (6158) Switches (9781) Wireless (45) Technology Control and Instrumentation (890) Electromechanical (9303) Magnetic (538) Platinum thin film (56) Thick Film (1372) More		TruStability® SSC Series-Standard Accuracy, ±2% total error band, digital I <sup>2</sup> C address: 0x28, SMT, AN: single axial barbed port, gage, 0 bar to 10 bar, 5.0 Vdc, dry gases only, diagnostics on				Customer Service Technical Support Global Sales & Serv View Site Demo Site Comments?	
		Actual product appearance may vary.				VIDEO - Dr. Larry Goldstein explains our newest and best technologies. Meet Dr. Larry	
			Sales & Service 🥥	Distributor Invento	ory 🥹	Moor Dr. Larry	my link
new products New Wireless Products Go farther, Work smarter, Explore new bossibilities, Just by cutting the cord and making the switch.		Overview Specs Documer Product Specifications	tation Application Notes			Login to iCOM Login to Rep/AD Po Login to Digital Univ	
		Measurement Type     Gage       Signal Conditioning     Amplified       Pressure Range     0 bar to 10 bar			_	News Cent	
		Overpressure Supply Voltage Supply Current Temperature Compensation	17 bar 5.0 Vdc 2 mA typ. Yes			HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIE: UNCOMPENSATED / UNAMPLIFIED BOARD MOUN PRESSURE SENSORS	
Wireless Web Site VGLA and WPMM (YR6000™	find out more	Output Calibration Response Time Port Style Package Type	Yes 1 ms max. AN: single axial barbed p SMT	port		HONEYWELL EXP LIMITLESS™ PLAT THE LAUNCH OF I GLOBALLY AVAILA INDUSTRIAL WIRE RECEIVER	FORM WITH FS .BLE
white papers		Accuracy (Best Fit Straight Line) Shock Vibration	±0.25% MIL-STD-202F, Method 213B, Condition F MIL-STD-202F, Curve AK (20.7 g random)			HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA	
Wireless Switches Offer Unlimited Benefit Basic Switches Are Not Created		Operating Temperature Compensated Temperature Range	Compensated Temperature Range -20 °C to 85 °C [-4 °F to 185 °F]			OPTION	
Equal Applying Precision Switches Sensors for Medical Devices New Ways to Measure Torque		Storage Temperature Media Compatibility Comment Availability	-40 °C to 85 °C [-40 °F to 185 °F] Dry gases only Diagnostics on Global			MICRO SWITC Anniversary s	
Choosing Safety Switches Specifying Hour Meters		Series Name	TruStability® SSC				

Need help?

Click here to contact us

Terms & Conditions | Privacy Statement | Site Map