

The Mini-Mox resistor is very versatile, covering a wide resistance range as well as a wide range of operating voltages. Provided with tolerances down to 0.1%, the Mini-Mox resistor works well in precision circuits.

## SPECIFICATIONS

### Material

**Resistor:** Metal Oxide

**Coating:** Silicone

**Core:** Alumina

**Terminals:** Solder-coated axial lead

### Electrical

#### Resistance Range:

250Ω to 1 Teraohm

**Power Rating:** 0.25W to 1.5W

**Voltage Rating:** 500V to 7.5KV

**Tolerance:** 0.1% to 20%

#### Operating Temperature:

-55°C to +220°C

#### Temperature Coefficient:

25ppm/°C 0° to 85°C available

## FEATURES


- Wide resistance ranges
- Silicone or epoxy coating
- Metal oxide resistive element

## APPLICATIONS

- Avionics
- Medical electronics
- High gain feedback applications
- Current pulse limiters
- Vacuum and space application

# Mini-Mox Resistors

## Precision Thick Film Axial Lead High Voltage/High Resistance Resistors




Ohmite Series	Resistance Range (Ohms)	Power @70°C	Voltage Rating	Available Tolerances*	A ± 0.015" (in/mm)	B max. (in/mm)
<b>• High-temperature (silicone coated)</b>						
MOX-400-22	500Ω to 300,000M	0.35W	2,500V	1% to 20%	0.520" / 13.21	0.140" / 3.56
MOX-750-22	750Ω to 600,000M	0.70W	5,000V	1% to 20%	0.820" / 20.83	0.140" / 3.56
MOX1125-22	1K to 1,000,000M	1.40W	7,500V	1% to 20%	1.210" / 30.73	0.140" / 3.56
*Some tolerances are not available over the entire resistance range.						
<b>• Standard (epoxy coated) @25°C</b>						
MOX-400-23	500Ω to 300,000M	0.75W	2,500V	0.25% to 20%	0.580" / 14.78	0.165" / 4.19
MOX-750-23	1K to 600,000M	1.00W	5,000V	0.25% to 20%	0.880" / 22.35	0.165" / 4.19
MOX1125-23	1K to 1,000,000M	1.50W	7,500V	0.25% to 20%	1.270" / 32.26	0.165" / 4.19

## PERFORMANCE DATA

Characteristic	Test Method	Specification
Humidity	MIL-STD-202, Method 103B, Condition B	±0.25%
Dielectric Withstanding Voltage	MIL-STD-202, Method 301, 750V	±0.25%
Insulation Resistance	MIL-STD-202, Method 302, Condition A or B	>10,000M or greater dry
Thermal Shock	MIL-STD-202, Method 107G, Condition B, B-1, or F	±0.20%
Load Life	MIL-STD-202, Method 108A, Condition D	±2.0%
Resistance to Solvents	MIL-STD-202, Method 215G	Acceptable for the Standard Series Only
Terminal Strength	MIL-STD-202, Method 211A, Condition A or B	±0.25%
Shock (Specified Pulse)	MIL-STD-202, Method 213B, Condition I	±0.25%
Vibration, High Frequency	MIL-STD-202, Method 204D, Condition D	±0.20%
Power Conditioning	MIL-R-49462A, Par 4.8	±0.50%
Solderability	MIL-STD-202, Method 208F	>95% Coverage

## DERATING



## STANDARD TEMPERATURE/VOLTAGE COEFFICIENTS OF RESISTANCE

Resistor Series	Temp. Coeff. of Resistance*			Voltage Coeff. of Resistance**	
	25 PPM/°C	50 PPM/°C	100 PPM/°C	< 2PPM/Volt	< 5PPM/Volt
MOX-400	1K-1,500M	1K-450M	451M-30,000M	1K-1,000M	1,001M-100,000M
MOX-750	1K-1,500M	1K-900M	901M-70,000M	1K-2,000M	2,001M-100,000M
MOX1125	1K-1,500M	1K-1,350M	1,351M-100,000M	1K-3,000M	3,001M-100,000M

\*Epoxy: -55°C to 110°C; High Temp. Silicone: -55°C to 210°C

\*\*For tighter VCs please contact factory.

## ORDERING INFORMATION

**MOX 1125 23 1006 F E**

**Style:** 200, 300, 400, 750, 1125

**Coating:** 2 = Black silicone, 3 = Epoxy, 6 = No coating

**E = RoHS compliant Available Jan. 2006**

**Mini Mox Series:** 0 = MOX-200 or 300; MOX-200 Z or 300 Z = 50ppm; 2 = 0.020"; 7 = 0.032"

**Ohms:** First 3 digits are significant; 4th digit is multiplier (# of zeroes to follow). Examples: 10R2 = 10.2 ohms; 1000 = 100 ohms; 1503 = 150,000 ohms

**Tolerance:** D = 0.5%, F = 1%, G = 2%, J = 5%, K = 10%, M = 15%, P = 20%