

Components of electronic housing - UM-PRO PCB C-LOCK L3 BK - 2200166

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Locking element for locking the PCB onto UM-PRO housing at level 3

The figure shows the versions for PCB level 1

Your advantages

- Available in individual lengths
- Available in the overall widths of 72 mm, 108 mm, and 122 mm
- ✓ Variety of connection technologies
- ☑ Can be mounted on the DIN rail



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	4 046356 547604
GTIN	4046356547604
Weight per Piece (excluding packing)	0.400 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General



Components of electronic housing - UM-PRO PCB C-LOCK L3 BK - 2200166

Technical data

General

Housing type	Press-drawn section housings
Housing material	Polyamide
Color (RAL)	black

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (operation)	1-40 C 103 C (depending on power dissipation)

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27182701
eCl@ss 4.0	27180400
eCl@ss 4.1	27180400
eCl@ss 5.0	27180500
eCl@ss 5.1	27180500
eCl@ss 6.0	27180800
eCl@ss 7.0	27182701
eCl@ss 8.0	27182701
eCl@ss 9.0	27182701

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002608
ETIM 5.0	EC002779
ETIM 6.0	EC002779
ETIM 7.0	EC002779

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501



Components of electronic housing - UM-PRO PCB C-LOCK L3 BK - 2200166

Classifications

UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized



http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

FILE E 240868

Phoenix Contact 2019 @ - all rights reserved http://www.phoenixcontact.com