

# Feed-through header - MCO-EH 1,5/5 G1L-3,5 GY7035 - 2202330

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCB headers, number of positions: 5, pitch: 3.5 mm, Article with lateral pin exit



## Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626051345
Weight per Piece (excluding packing)	3.600 g
Custom tariff number	85366930
Country of origin	Poland

## Technical data

### Dimensions

Pitch	3.5 mm
Length of the solder pin	2 mm

### General

Range of articles	MCO 1,5/...G1L
Insulating material group	I
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	125 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	320 V

# Feed-through header - MCO-EH 1,5/5 G1L-3,5 GY7035 - 2202330

## Technical data

### General

Nominal current I <sub>N</sub>	8 A
Insulating material	PA
Number of positions	5

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

### ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002637
ETIM 5.0	EC002637
ETIM 6.0	EC002637
ETIM 7.0	EC002637

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121409

## Approvals

### Approvals

## Feed-through header - MCO-EH 1,5/5 G1L-3,5 GY7035 - 2202330

### Approvals

Approvals

EAC

---

Ex Approvals

---

### Approval details

EAC		B.01742
-----	---	---------

---