


Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)





Product Description

Mounting set, consisting of battery frame for universal wall mounting or surface mounting, 2 x cross dowel (M6) with collar, 2 x screw (M6 x 140), 2 x washer (6.4 x 12), 1 x battery retaining bracket with fixing bracket, and 4 x screw (M3 x 14).



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 933131
GTIN	4046356933131
Custom tariff number	73269098
Country of origin	Germany

Technical data

General

Net weight	5 kg
5 , ,	

Dimensions

Width	464 mm
Height	201 mm
Depth	205 mm

Standards and Regulations

Shock	IEC 60068-2-27



Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Technical data

Standards and Regulations

Vibration (operation)	GL (Germanischer Lloyd)
-----------------------	-------------------------

Classifications

eCl@ss

eCl@ss 4.1	27040603
eCl@ss 5.1	27242213
eCl@ss 6.0	27040603
eCl@ss 8.0	27379201
eCl@ss 9.0	27379201

ETIM

ETIM 4.0	EC002498
ETIM 5.0	EC002498
ETIM 6.0	EC002498

UNSPSC

UNSPSC 13.2	39121421
UNGF3C 13.2	39121421

Approvals

Approvals

Approvals

ABS / BV / DNV GL / LR

Ex Approvals

Approval details

ABS http://www.eagle.org/eagleExternalPortalWEB/ 15-GD1438179-PDA

BV



http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials

41516/A0 BV



Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Approvals

DNV GL	http://exchange.dnv.com/tari/	61457-13 HH
mm²/AWG/kcmil	6	
Nominal current IN	41 A	
Nominal voltage UN	500 V	

LR Llovd's http://www.lr.org/en	17/20032
---------------------------------	----------

Accessories

Accessories

Battery unit

Energy storage - UPS-BAT/VRLA-WTR/24DC/13AH - 2320416



Energy storage device, lead AGM, VRLA technology, 24 V DC, 13 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

Energy storage - UPS-BAT/VRLA-WTR/24DC/26AH - 2320429



Energy storage device, lead AGM, VRLA technology, 24 V DC, 26 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

Energy storage - UPS-BAT/VRLA/24DC/38AH - 2320335



Energy storage device, lead AGM, VRLA technology, 24 V DC, 38 Ah, automatic detection, and communication with QUINT UPS-IQ



Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com