

## Surge protection device - TT-UK5/ 24DC - 2794699

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular terminal block with surge voltage fine protection between clamping connector and DIN rail, nominal voltage: 24 V DC, for mounting on NS 32 or NS 35/7.5, terminal width: 6.2 mm, terminal height: 47 mm

### Product Features

- Can be used in the signal circuits of electronic controllers



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 072872
Weight per Piece (excluding packing)	11.28 g
Custom tariff number	85363030
Country of origin	Greece

### Technical data

#### Environmental Product Compliance

REACH SVHC	4-Nonylphenol, ethoxylated
------------	----------------------------

#### Dimensions

Height	47 mm
Width	6.2 mm
Length	42.5 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

#### General

Housing material	PA
------------------	----

## Surge protection device - TT-UK5/ 24DC - 2794699

### Technical data

#### General

Flammability rating according to UL 94	V-2
Color	black
Mounting type	DIN rail: 35 mm
Type	Single-level terminal block
Number of positions	1
Direction of action	Line-Earth Ground

#### Protective circuit

IEC test classification	C3
VDE requirement class	C3
Nominal voltage $U_N$	24 V DC
Maximum continuous voltage $U_C$	28 V DC
	20 V AC
Maximum continuous voltage $U_C$ (wire-ground)	28 V DC
	20 V AC
Nominal current $I_N$	32 A (50 °C)
Residual current $I_{PE}$	$\leq 5 \mu A$
Nominal discharge current $I_n$ (8/20) $\mu s$ (Core-Earth)	169 A
Total surge current (8/20) $\mu s$	169 A
Max. discharge current $I_{max}$ (8/20) $\mu s$ maximum (Core-Earth)	169 A
Nominal pulse current $I_{an}$ (10/1000) $\mu s$ (Core-Earth)	33 A
Output voltage limitation at 1 kV/ $\mu s$ (Core-Earth) spike	$\leq 40 V$
Output voltage limitation at 1 kV/ $\mu s$ (Core-Earth) static	$\leq 40 V$
Residual voltage at $I_n$ (conductor-ground)	$\leq 55 V$
Response time $t_A$ (Core-Earth)	$\leq 1 ns$
Cut-off frequency $f_g$ (3 dB), asym. (PE) in 150 Ohm system	typ. 1.2 MHz
Capacity (Core-Earth)	$\leq 1.35 nF$
Impulse durability (conductor-ground)	C3 (25 A)

#### Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section solid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>

# Surge protection device - TT-UK5/ 24DC - 2794699

## Technical data

### Connection data

Conductor cross section AWG	24 ... 12
-----------------------------	-----------

### Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

## Classifications

### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

### ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

## Approvals

### Approvals

#### Approvals

CSA / UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

# Surge protection device - TT-UK5/ 24DC - 2794699

## Approvals

Ex Approvals

Approvals submitted

### Approval details

CSA	
mm <sup>2</sup> /AWG/kcmil	28-10
Nominal current I <sub>N</sub>	34 A
Nominal voltage U <sub>N</sub>	24 V

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	26-10
Nominal current I <sub>N</sub>	30 A
Nominal voltage U <sub>N</sub>	24 V

cUL Recognized	
mm <sup>2</sup> /AWG/kcmil	26-10
Nominal current I <sub>N</sub>	30 A
Nominal voltage U <sub>N</sub>	24 V

EAC
-----


EAC
-----

cULus Recognized
------------------

# Surge protection device - TT-UK5/ 24DC - 2794699

## Drawings

Circuit diagram



## Surge protection device - TT-UK5/ 24DC - 2794699

Schematic diagram

