

Fuse - FUSE 10,3X38 4A PV - 3061305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse, 10.3x38 mm, up to 1000 V DC, gPV characteristics

Your advantages

- ✓ 10 x 38 midget fuses for reliable protection of PV modules and their control system
- ✓ Use in PV lines with a nominal voltage of up to 1000 V DC
- ✓ Designed in accordance with the photovoltaic standard IEC 60269-6

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 523639
GTIN	4046356523639
Weight per Piece (excluding packing)	8.000 g
Custom tariff number	85361010
Country of origin	Slovenia

Technical data

General

Color	white
Flammability rating according to UL 94	V0
Maximum power dissipation for nominal condition	1.27 W

Dimensions

Length	38 mm
--------	-------

Fuse - FUSE 10,3X38 4A PV - 3061305

Technical data

Dimensions

Diameter	10.3 mm
----------	---------

General

Fuse	Midget / 10.3 x 38
Connection in acc. with standard	IEC 60269-6
Nominal current I _N	4 A
Nominal voltage U _N	1000 V DC

Standards and Regulations

Connection in acc. with standard	IEC 60269-6
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27142000
eCl@ss 6.0	27142000
eCl@ss 7.0	27142002
eCl@ss 8.0	27142002
eCl@ss 9.0	27142002

ETIM

ETIM 3.0	EC000035
ETIM 4.0	EC002704
ETIM 5.0	EC002704
ETIM 6.0	EC002704
ETIM 7.0	EC002704

UNSPSC

UNSPSC 6.01	30211915
UNSPSC 7.0901	39121514
UNSPSC 11	39121514
UNSPSC 12.01	39121514
UNSPSC 13.2	39121627

Fuse - FUSE 10,3X38 4A PV - 3061305

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------
