## 1.15.106.301/0410



# Pushbutton, 9.1 mm, 1NO+1NC, yellow



#### fields of application

- > Mechanical and system engineering
- > Model construction
- > Home technology

## description

Pushbutton with mounting hole diameter 9.1 mm

Pushbutton with mounting hole diameter 9.1 mm, 1 NC + 1 NO

## technical data

>	general
---	---------

illuminated No Bezel color yellow

Collar shape round -25 °C Operating temperature, min. Operating temperature, max. 70 °C Storage temperature, min. -40 °C 80 °C Storage temperature, max. Soldering time for manual 3 sec

soldering, max.

Soldering temperature for manual 350 °C

soldering

Soldering Manual soldering

Packaging Box Packaging unit 10 pcs. net weight 2.3 g

200,000 Cycles Operating life

Degree of protection, front side,

according to DIN EN 60529

RoHS compliant Yes **REACH** compliant Yes direct links

> RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.  $\textbf{date} : \text{Aug 25, 2019} \ \textbf{page} : 1/2$ 

**IP40** 

RAFI GmbH & Co. KG

# 1.15.106.301/0410



## > mounting diameters

Mounting hole 9.1 mm Mounting depth 25 mm Installation height 7 mm Outside dimension, width 11 mm

#### > mechanical data

Actuation function momentary contact function

Operating force, max. 5 N Operating force, min. 5 N Operating travel, max. 1.5 mm Contact function 1 NC + 1 NO Contact system Bridge contact

Contact material Gold

Threaded ring Fixing Terminal on the rear Solder terminal

Lötbarkeit Yes

> electrical data

Rated voltage, max. 24 V Rated current, max. 0.1 A