

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Isobar 2-Outlet Surge Protector, Direct Plug-In, 1410 Joules, Diagnostic LEDs, Black Metal Housing

MODEL NUMBER: ULTRABLOK











Premium protection for A/V home theater components and computer peripherals against dangerous power surges, spikes and line noise. Recommended for home theaters and home offices.

Description

Premium protection for your expensive computer and audio/visual equipment, the ULTRABLOK Isobar® 2-Outlet Surge Protector features a surge protection rating of 1410 joules to defend your sensitive electronics against even the strongest surges and spikes. In fact, Tripp Lite will repair or replace any connected equipment damaged by surges, including direct lightning strikes, up to \$10,000 for life (valid in the U.S., Canada and Puerto Rico only).

The ULTRABLOK features two NEMA 5-15R outlets, perfect for your flat-panel HDTV and Blu-ray™ player or a pair of computer peripherals, such as a printer and a router. This unit's unique protection system prevents disruptive line noise from causing A/V distortion, computer lock-ups, data errors and similar problems. Large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors remove EMI/RFI interference and prevent system crashes, reboots and performance problems.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the ULTRABLOK protects all three, covering two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in the event of an overload. Diagnostic LEDs show power, protection and line fault status at a glance. The ULTRABLOK plugs directly into any standard NEMA 5-15R outlet. Optional mounting hardware is included for permanent attachment to the outlet cover, which will prevent the ULTRABLOK from coming loose accidentally.

Highlights

- 2 NEMA 5-15R surge-protected outlets
- 1410-joule surge protection rating
- Durable metal housing mounts out of sight behind furniture
- 15A resettable circuit breaker prevents dangerous overloads
- Plugs directly into outlet with no power cord

Package Includes

- ULTRABLOK Isobar 2-Outlet Surge Protector, Black Metal Housing
- Mounting hardware
- Owner's manual



Features

1410-Joule Surge Protection for Your Home Theater and Office ElectronicsProtects your components against surges and spikesFull normal mode (H-N) and common mode (N-G/H-G) line surge suppression2 NEMA 5-15R surge-protected outletsExceeds IEEE 587 Category A and B surge suppression specifications

Premium Safety FeaturesAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LEDs confirm power, protection and ground status at a glanceConforms to current UL 1449 3rd Edition safety standards

Fits Effortlessly Into Your SetupPlugs directly into standard NEMA 5-15R outlet with no power cordOptional hardware included for permanent mounting to outlet coverMetal housing designed for long life.

Backed by Tripp Lite's Ultimate Lifetime Insurance\$10,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332010476	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(2) 5-15R	
Circuit Breaker (amps)	15	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Length Details	Direct plug-in	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Diagnostic LED Details	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)	





SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1410	
AC Suppression Response Time	NM = 0 ns. CM = <1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	140	
AC Suppression Surge Current Rating	48,000 amps	
AC Suppression Components Used	Metal oxide varistors, toroidal balanced chokes and VHF capacitors	
Safe Thermal Fusing	Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurences	
EMI / RFI Filtering	40-80 dB	
Immunity	Conforms to IEE 587 / ANSI C62.41	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Anti-Microbial Protected	No	
Color	Black	
Form Factors Supported	Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket	
Housing Color	Black	
Included Mounting Accessories	Mounting hardware	
Integrated Keyhole Mounting Slots	No	
Material of Construction	Metal	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	13.72 x 6.60 x 9.91	
Shipping Dimensions (hwd / in.)	5.40 x 2.60 x 3.90	
Shipping Weight (kg)	0.36	
Shipping Weight (lbs.)	0.80	
Unit Dimensions (hwd / cm)	10.16 x 6.35 x 6.35	
Unit Dimensions (hwd / in.)	4 x 2.5 x 2.5	
Unit Weight (kg)	0.36	
Unit Weight (lbs.)	.8	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

SPECIAL FEATURES		
Rotatable Outlets	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	Tested to UL1449 3rd Edition by ETL	
Canada	Approved for Canada by ETL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies