

**Screwdriver
SDS 0.4X2.0X60**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Slotted screwdriver with rounded blade SD DIN 5265,
ISO 2380/2, output to DIN 5264, ISO 2380/1.
ChromTop tip, SoftFinish grip

General ordering data

| | |
|------------|---|
| Type | SDS 0.4X2.0X60 |
| Order No. | 9037160000 |
| Version | Screwdriver, Blade width (B): 2 mm, Blade length: 60 mm, Blade thickness (A): 0.4 mm |
| GTIN (EAN) | 4032248171613 |
| Qty. | 1 pc(s). |

Creation date April 21, 2020 1:38:37 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

**Screwdriver
SDS 0.4X2.0X60**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|----------|--------|----------------|------------|
| Width | 170 mm | Width (inches) | 6.693 inch |
| Weight | 32 g | Net weight | 26.9 g |
| Diameter | 23 mm | | |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Screwing tools

| | | | |
|--------------|---------|---------------------|--------|
| Blade length | 60 mm | Blade thickness (A) | 0.4 mm |
| Blade type | B | Blade width (B) | 2 mm |
| Form | Slotted | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000158 | ETIM 7.0 | EC000158 |
| eClass 9.0 | 21-04-04-07 | eClass 9.1 | 21-04-04-07 |
| eClass 10.0 | 21-04-04-07 | UNSPSC | 27-11-17-01 |

Approvals

Approvals



Downloads

Brochure/Catalogue [CAT 3 HDC 17/18 EN](#)
[CAT 6 TOOLS 15/16 EN](#)
[CAT 5 ENCL 17/18 EN](#)
[CAT 1 TERM 16/17 EN](#)